



## 2015 Realm FS6 (45' K3GT)

### Premium Chassis Features

- Power Tilt and Telescope Steering Column
- SMART Steering Wheel with Leather/Wood Grain
- Radio Controls on Steering Wheel
- Electronic Ride Height Control Valves
- Passive Steer Tag Axle
- Side Mounted Service Center
- Automatic Traction Control (ATC)
- Self Leveling System (SLS)
- 20,000 lb Towing Capacity
- 3 Year / 50,000 Mile Warranty:
  - No Deductible, 24/7 Roadside Assistance
- Lifetime Warranty on Frame & Cross Members

Chassis Weight Rating	GVWR	Front GAWR	Rear GAWR	Tag GAWR	GCWR
	54,000 lb	20,000 lb	20,000 lb	14,000 lb	74,000 lb

Engine	Peak Horsepower	Peak Torque
Cummins 2013 ISX15 <ul style="list-style-type: none"> <li>• 18.7 CFM Air Compressor</li> <li>• 1,500 Watt Block Heater</li> </ul>	600 hp @ 1,800 rpm	1,950 lb-ft @ 1,200 rpm

Transmission	Ratios: 1st	2nd	3rd	4th	5th	6th	Rev
Allison GEN 5 - 4000MH Electronic, 6-Speed with (2) Overdrives Push-Button Shift Pad	3.51	1.91	1.43	1.00	0.74	0.64	-4.80

Front Axle	Capacity	Track Width
Reyco Granning IFS2000	20,000 lb	86.5"

Rear Axle	Capacity	Track	Ratio	Tag Axle Capacity	Tag Track
Dana S23-190	23,000 lb	72.7"	4.30:1 "Quiet-Gear"	14,000 lb	85.3"

Suspension	Shock Absorber
<b>Front:</b> Reyco Granning IFS2000 <b>Rear:</b> Reyco Granning RD2300NR <b>Tag:</b> Reyco Granning RTS1400	Bilstein Shocks Front: 46mm Rear: 46mm Tag: 46mm

Brakes	Parking	Auxiliary	ABS
Air Disc Brakes	Push/Pull Knob	Three-Stage Engine Compression Brake	WABCO 6S/6M ABS System



# 2015 Realm FS6 (45' K3GT)

<b>Steering</b>	Column	Gear	Turn Angle
VIP Soft Touch, Wood Grain & Leather-Wrapped Smart Wheel w/Integrated Radio Controls	Electric Douglas Tilt and Telescoping	TAS-85 RCS-85	55°
<b>Cooling System</b>			
Side-Mounted Radiator: 1,891 sq.in. Parallel Air Flow System with Low Profile Radiator, Charge Air Cooler and Integrated A/C Condenser Utilizing a Modulated Engine-Driven Cooling Fan			
<b>Electrical System</b>	Alternator	Batteries	
Custom Modular Electrical System	270 amp Leece-Neville Alternator	(2) Harris 950 CCA Batteries	
<b>Frame</b>	Top Rail	Bottom Rail	
Trussed, Torque-Box Structured Frame Design for Frame Strength, Reduced Camber and Improved Storage Capacity	N/A	<b>Front:</b> 14.25" x 3.5" x .31" <b>Rear (Rail):</b> 12.75" x 3.5" x .31" <b>Rear (Tube):</b> 10.0" x 3.0" x .25"	
<b>Fuel System</b>			
<ul style="list-style-type: none"> <li>• 200 gal Fuel Tank with Dual Side Fill</li> <li>• Side-Mounted Fuel Level Sender</li> <li>• 15 gal DEF Tank</li> </ul>			
<b>Wheel Base</b>	Front Overhang	Rear Overhang	
316"	76"	126"	
<b>Wheels</b>			
(6) Alcoa Dura-bright Aluminum Wheels with Dress Kit (2) Steel Wheels on Inside Dual Wheels			
<b>Tires</b>			
<b>Front:</b> Michelin 365/70R22.5 XZA LRL <b>Rear:</b> Michelin 315/80R22.5 XZA1 LRL <b>Tag:</b> Michelin 315/80R22.5 XZA1 LRL			

The information in this literature reflects product specifications at the date of printing. Spartan Chassis and its OEMs reserve the right, at any time, to make changes in product design, material or component specifications as its sole option, without notice. All information printed in this literature is subject to change.

Printed 6/2014

